

Type Min/Max actuators





## FOR CONSTANT VOLUME FLOWS WITH VMIN/VMAX SWITCHING IN AIR CONDITIONING SYSTEMS

Actuators for mechanical self-powered CAV controllers Type EN, RN, or VFC, and for flow adjustment dampers Type VFR

- Switching between two volume flow setpoint values, e.g. for daytime and night-time operation
- Supply voltage 24 V AC/DC or 230 V AC
- Control input signal: 1-wire control or 2-wire control (3-point)
- Potentiometer or mechanical stops
- Positive lock connection with CAV controller
- Retrofit possible

### Application

- Actuators for min/max switching
- Switching between volume flow setpoint values of mechanical self-powered CAV controllers Type RN, EN or VFC
- Change of the damper blade positions of flow adjustment dampers Type VFR

### Parts and characteristics

- Potentiometer or mechanical stops for setting the volume flow rate setpoints
- Supply voltage 24 V AC/DC or 230 V AC
- Overload protection
- 1-wire control or 2-wire control (3-point)
- Optional auxiliary switch for capturing the end positions

## TECHNICAL INFORMATION

Function, TECHNICAL DATA, Produktbeziehungen 

---

Variants 

---

Electrical connection 

---

### TROX Australia Pty Ltd

---



TROX Australia Pty Ltd  
Level 32  
101 Miller Street  
North Sydney 2060  
New South Wales, Australia.

Telephone number +61 2 8923 2551

### Online-Services

---

- [Your contact partner](#)

---

- [Locations Australia](#)

---

### Service-Hotlines

---

Main Office and Factory Number

Tel: +61 (02) 8923 2551

[Management APO](#)

[TROX IN SOCIAL WEB](#)

---