

Type LVS



FOR EXTRACT AIR

Circular disc valves with manually adjustable annular gap

- Nominal sizes 100, 125, 160, 200 mm
- Volume flow rate range 10 – 50 l/s or 36 – 180 m³/h
- Diffuser face made of formed sheet steel, powder-coated
- For variable and constant volume flows
- For ceiling and wall installation
- Easy to install
- Volume flow rate balancing by simply turning the valve disc
- Inexpensive solution for small rooms

Application

- Type LVS disc valves are used as extract air devices in small rooms
- For variable and constant volume flows
- For walls and suspended ceilings

Special characteristics

- Continuous volume flow rate balancing by turning the valve disc
- Easy to install

Nominal sizes

- 100, 125, 160, 200

Parts and characteristics

- Valve disc with threaded spindle and lock nut
- Valve casing including cross bar with orifice for the threaded spindle
- Installation subframe that accommodates the disc valve

Materials and surfaces

- Valve casing and valve disc made of galvanised sheet steel
- Installation subframe, cross bar, threaded spindle and lock nut made of galvanised steel
- Foam seal
- Valve casing and valve disc powder-coated RAL 9010, pure white

Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022

TROX Australia Pty Ltd



TROX Australia Pty Ltd
Level 32
101 Miller Street
North Sydney 2060
New South Wales, Australia.

Telephone number +61 2 8923 2551

Online-Services

- > [Your contact partner](#)
-
- > [Locations Australia](#)
-

Service-Hotlines

Main Office and Factory Number

Tel: +61 (02) 8923 2551

[Management APO](#)

TROX IN SOCIAL WEB
