

## TYPE QSH · ISH

- TROX displacement flow diffusers type QSH/ISH are primarily used in industrial manufacturing and installed as free hanging units.
- They can be adjusted individually for any temperature range.



### PRODUCT DESCRIPTION ^

TROX displacement diffusers type QSH · ISH are suitable for heating and cooling mode. The discharge direction is adapted to the operational situation by means of an integrated adjusting mechanism.

The diffusers can be operated by hand (chain pull) or by means of different variants of electric actuators. Automatic adjustment (without auxiliary energy) is also possible.

In the case type ISH, the cold air is discharged horizontally at high momentum. These displacement diffusers are ideal when varying supply air temperature differentials in the range from -8 K to +12 K apply, at installation heights of 3.5 to 10 m.

### Technology v

circular

195 – 2,220 l/s

700 – 8,000 m<sup>3</sup>/h

415 – 4,706 cfm

Ø 250 – 560 mm

TROX Australia Pty Ltd

---



TROX Australia Pty Ltd  
Level 32  
101 Miller Street  
North Sydney 2060  
New South Wales, Australia.

Telephone number +61 2 8923 2551

Online-Services

---

- › [Your contact partner](#)
  - › [Locations Australia](#)
- 

Service-Hotlines

---

Main Office and Factory Number

Tel: +61 (02) 8923 2551

[Management APO](#)

[TROX IN SOCIAL WEB](#)

---